

At your side.
brother®

Twin Needle/Three Needle Feed Off
The Arm Double Chain Stitcher

DA-9270
DA-9280



Narrow Cylinder Bed Feed Off-the-arm Double Chain Stitchers

Ideal for a wide range of materials from shirts to jeans

Doppelkettenstich-Nähmaschine mit schmalem Zylinderbett und Armvorschubvorrichtung

Ideal für verschiedenstes Nähgut von Hemden bis Jeans

Machines à point de chaînette double à bras déporté libre étroit

Convient parfaitement à une grande gamme de tissus, des chemises aux jeans

Máquina de coser cadeneta doble de alimentación por el brazo y cama cilíndrica angosta

Ideal para coser una gran variedad de materiales desde faldas a jeans

These twin-needle and three-needle double chainstitchers are updated versions of previous models, with improved basic functions. They are ideal for use in sewing cylindrical articles.

The 9270 is ideal for use in sewing thin to medium-thick materials, and also lets you sew attractive balloon stitches onto thin materials, without puckering.

The 9280 is suitable for sewing thick to extra-heavy materials. A tractor-type presser foot which is ideal for folded material can be used to easily ride over thick sections, even 16 layers or more of 14-ounce denim. It can also sew at a maximum sewing speed of 4,000 rpm.

In addition, separate adjustment-type loopers can be easily adjusted, and a movable needle guard effectively prevents skipped stitches from occurring. Improvements such as these in the gauge parts mean that workability is also greatly improved.



DA-9270



DA-9280

TWIN NEEDLE/THREE NEEDLE FEED OFF THE ARM DOUBLE CHAIN STITCHER
 ZWEINADEL/DREINADEL-DOPPELKETTENSTICH-ARMABWÄRTSMASCHINE
 MACHINE BRAS DEPORTE-POINT DE CHAINETTE DOUBLE 2/3 AIGUILLES
 MAQUINA DE DOS/TRES AGUJAS DE BRAZO CADENETA

DA-9270
DA-9280




Handles small cylindrical articles too
Auch für kleine röhrenförmige Artikel
Les petits articles cylindriques peuvent aussi être traités
También sirve para artículos cilíndricos pequeños

The outer diameter of the cylinder is a slim 171 mm, with extra consideration given to the ease of use by the operator.



Full pushbutton operation
Tastenvollbedienung
Fonctionnement entièrement commandé par boutons-poussoirs
Ajuste completo mediante botón pulsador

The stitch length can be changed simply by pressing a button while turning the machine pulley to align the scale marks.



Attractive balloon stitches
Attraktive Ballonstiche
Points ballon attrayants
Atractivas puntadas tipo globo

Low-tension sewing gives an attractive finished appearance to balloon stitches. It also produces pliant seams and prevents puckering.



Movable needle guards requires no adjustment
Beweglicher Nadelchutz braucht nicht einzustellen zu werden
Les garde-aiguilles mobiles ne nécessitent aucun réglage
Protectores de agujas móviles libres de ajustes

A movable needle guard has been adopted in order to prevent skipped stitches from occurring. The movable needle guard timing and feed mechanism timing are fully coordinated, so that no adjustment is necessary even if the stitch length is changed. (It may be required to readjust the position of the movable needle guard according to materials and thread.)



9270-A

Options



Puller device

This device accurately feeds thick sections of material or material which is normally difficult to feed, thus preventing misaligned and puckering from occurring.



Needle thread cooler









The needle thread cooler cools the needle thread using silicon oil in order to prevent thread breakages due to heat.



Chain cutter

Cuts the thread at the same time as the sewing end is reached, providing increased work efficiency. 9270 (excepting fixed needle guard spec.) and 9280-C, -D spec. are available.

●Specifications

Model								
	Double chain stitch	Stitch length	Height of presser foot	Light materials	Medium materials	Heavy materials	Extra heavy materials	Max. sewing speed
DA-9270	★	For light materials 3.0mm For medium materials 3.5mm	10mm	★	★	—	—	4,000* ¹ rpm
DA-9280	★	4.2mm	11mm	—	—	★	★	4,000* ¹ rpm (Normally 3,600 rpm)

* ¹ If the puller device is being used, the maximum sewing speed is 3,600 rpm.

* ² The 9280 should normally be operated at a sewing speed of 3,600 rpm. when operating it at 4,000 rpm, the optional needle thread cooler should be fitted.

DA-9270 -

Applications		No. of needles		Needle gauge*		Needle
1	Light materials	2	2-needles	48	4.8mm(3/16)	TV×64#12
				64	6.4mm(1/4)	
2	Light-medium materials	2	2-needles	30	3.2mm(1/8)	TV×64#14
				40	4.0mm(5/32)	
				48	4.8mm(3/16)	
3	Medium materials	2	2-needles	64	6.4mm(1/4)	TV×64#16
A	Light materials, with puller	2	2-needles	48	4.8mm(3/16)	TV×64#11PSU
				64	6.4mm(1/4)	
		3	3-needles	64	6.4mm(1/4)	TV×64#11PSU

DA-9280 -

Applications		No. of needles		Needle gauge*		Needle
5	Heavy materials	2	2-needles	48	4.8mm(3/16)	TV×5#21
				56	5.6mm(7/32)	
		3	3-needles	64	6.4mm(1/4)	TV×5#21
				80	8.0mm(5/16)	
				96	9.6mm(3/8)	
7	Extra heavy materials (denim)	2	2-needles	64	6.4mm(1/4)	TV×5#22
				64	6.4mm(1/4)	
		3	3-needles	80	8.0mm(5/16)	TV×5#22
C	Heavy materials, with puller	2	2-needles	48	4.8mm(3/16)	
				64	6.4mm(1/4)	TV×5#21
D	Extra heavy materials (denim), with puller	2	2-needles	64	6.4mm(1/4)	
				64	6.4mm(1/4)	TV×5#22
		3	3-needles	80	8.0mm(5/16)	
				96	9.6mm(3/8)	

*3-needle means total needle gauge

*Lapper size

For light materials: 3.2 mm, 4.0 mm, 4.8 mm, 6.4 mm

For medium materials: 3.2 mm, 4.0 mm, 4.8 mm, 5.6 mm, 6.4 mm, 8.0 mm, 9.6mm

For heavy materials: 4.8 mm, 5.6 mm, 6.4 mm, 8.0 mm, 9.6 mm

For extra heavy materials (denim): 6.4 mm, 8.0 mm, 9.6 mm

Product specifications are subject to change for improvement without notice. Please read instruction manual before using the machine for safety operation.

brother
BROTHER INDUSTRIES, LTD.

ARCH SEWING
215.627.1768
www.archsewing.com