

1-needle, Unison-feed, Long Arm Lockstitch Machine with a Large Hook

DNU-261H

With its generous 635mm of free space under the arm and powerful unison-feed, the machine delivers outstanding productivity when sewing tents and sheets.



Consistent seam quality

With its unison-feed mechanism that ensures a smooth and steady feed of materials, the machine provides consistent seam quality with no material slippage.



The machine head structure is designed to improve operability.

With the wide 635mm of free space under the arm, a large material can be sewn while spread over the bed.

The presser foot goes up as high as 15mm to ensure easy placements/removal of extra heavy-weight materials.



Increased alternating vertical movement of the walking foot and presser foot.

The alternating vertical movement of the walking foot and presser foot can be widely adjusted in the range of 3 to 6mm. With this feature, the machine is able to flexibly adapt to various kinds of heavy-weight materials.




Simple adjustment of normal/reverse stitch length.

Stitch length is adjustable by up to 8mm with a stitch dial. The stitch length is also adjustable for reverse-feed stitching.



The frequency of bobbin thread replacement is reduced.

Since the machine incorporates a horizontal-axis double-capacity hook, the frequency of bobbin thread replacement is reduced, further increasing efficiency.



SPECIFICATIONS

Max. sewing speed	1,500rpm
Max. stitch length	8mm (normal/reverse feed)
Needle bar stroke	38mm
Lift of the presser foot	By hand: 9mm, By knee: 15mm
Thread take-up	Slide type
Alternating vertical movement	3 ~ 6mm
Hook	Horizontal-axis full-rotary double-capacity hook
Needle (at the time of delivery)	DB x 17 (#23) #16 ~ #23, For JE: 135 x 17 (Nm160)
Thread	#40 ~ #8, B33 ~ B92, Nm=90/3 ~ 30/3
Lubrication	By an oiler (hook: automatic)
Lubricating oil	JUKI New Defrix Oil No.1 (equivalent to ISO VG7)
Distance from needle to machine arm	635mm
Bed size	850mm x 178mm
Weight of the machine head	59kg

WHEN YOU PLACE ORDERS

Please note when placing orders, that the model name should be written as follows:

DNU-261H- [] [] / []

Automatic reverse feed function	Code
Not provided	00
Provided	0B

Pneumatic auto-lifter (optional)	Code
Knee switch type (AK70A)	A
Pedal switch type (AK70B)	B
Not provided	

● To order, please contact your nearest JUKI distributor.

JUKI[®]
JUKI CORPORATION
INTERNATIONAL SALES H.Q.

8-2-1, KOKURYO-CHO, CHOFU-SHI,
 TOKYO 182-8655, JAPAN
 PHONE : (81) 3-3430-4001 ~ 4
 FAX : (81) 3-3430-4909.4914
 TELEX : J22967
 http://www.juki.co.jp

* Specifications and appearance are subject to change without prior notice for improvement.
 * Read the instruction manual before putting the machine into service to ensure safety.