

At your side.
brother®

CYLINDER BED NEEDLE FEED
DOUBLE CHAIN STITCHER
DC-2910

A quiet waistband sewing machine with excellent cost performance



A quiet waistband sewing machine with excellent cost performance

This is a cylinder bed needle feed double chain stitcher for sewing waistbands onto medium-heavy and heavy materials such as jeans.

A quiet sewing mechanism reduces noise during sewing, in order to create a more comfortable working environment.

The maximum sewing speed of 4,500 rpm, and adoption of an automatic lubrication system and a linked needle feed and lower feed mechanism are some of the features which make this machine easy to use and which provide excellent cost performance.

Eine geräuscharme Bundnähmaschine mit einem ausgezeichneten Preis/Leistungsverhältnis

Diese Freiarm-Doppelkettenstichnähmaschine mit Nadeltransport eignet sich zum Nähen von Bünden von mittelschwerem bis schwerem Material, wie Jeans.

Durch den Betrieb mit niedrigem Geräuschpegel ist für eine komfortable Arbeitsumgebung gesorgt. Eine maximale Nähgeschwindigkeit von 4500 Stichen pro Minute, ein automatisches Schmiersystem und ein synchronisierter Nadel- und Untertransport tragen zu einer vereinfachten Bedienung und einem ausgezeichneten Preis/Leistungsverhältnis bei.



Une machine à coudre les passants de ceinture silencieuse d'excellent rapport qualité/ prix

Cette machine canon point de chaînette double entraînement par aiguille permet de coudre les passants de ceinture sur les tissus mi-épais et épais tels que les jeans.

Cette machine silencieuse réduit les bruits lors de la couture, afin d'améliorer le confort de l'environnement de travail. La vitesse de couture maximum de 4.500 tours/mn, et l'adoption d'un système de lubrification automatique et d'un dispositif d'entraînement par aiguille et entraînement inférieur liés, sont quelques-unes des fonctionnalités qui rendent cette machine facile à utiliser et améliorent son rapport qualité/prix.

Una máquina de coser bandas de cinturas silenciosa con un excelente costo-rendimiento

Esta es una máquina de coser doble cadena-doble de alimentación por aguja de cama cilíndrica para costura de banda de cinturas de materiales pesados y medio-pesados como jeans.

Un mecanismo de costura silencioso reduce el ruido durante la costura, para crear un ambiente de trabajo más confortable. La velocidad máxima de costura es de 4.500 rpm, y la adopción de un sistema de lubricación automática y un mecanismo de alimentación por aguja articulada y alimentación inferior son algunas de las características que hacen de esta máquina muy fácil de usar y que le ofrecen una excelente relación costo-rendimiento.



DC-2910

CYLINDER BED NEEDLE FEED DOUBLE CHAIN STITCHER


ZYLINDERBETT-DOPPELKETTENSTICHMASCHINE MIT NADELTRANSPORT

MACHINE CEINTUREUSE CANON DOUBLE ENTRAINEMENT POINT DE CHAINETTE DOUBLE

MAQUINA CILINDRICA DOBLE CADENETA ALIMENTACION POR DIENTE


DC-2910-60-2E1A14

Quiet sewing operation
Geräuscharmer Betrieb
Fonctionnement silencieux
Funcionamiento de costura silencioso



- The forced lubrication system ensures that each bearing is lubricated by a film of oil at all times. As a result, sewing operation is very quiet even at the maximum sewing speed of 4,500 rpm.

Easy-maintenance automatic lubrication system
Einfache Wartung dank automatischem Schmiersystem
Système de lubrification automatique facile à entretenir
Sistema de lubricación automática de fácil mantenimiento



- A forced lubrication system that incorporates a trochoid pump has been adopted. This eases the maintenance work required for lubrication.
- Excess oil is constantly reclaimed by a plunger pump.

Easy feed adjustment
Einfache Transporteinstellung
Réglage facile de l'entraînement
Fácil ajuste de alimentación




- The needle feed and lower feed operate together. As a result, the needle feed and lower feed amounts can both be adjusted at the same time using a single pushbutton. Thus the sewing pitch can be changed very easily.




- The ratio between the needle feed amount and lower feed amount can also be changed easily, so that uneven material feeding can be fixed smoothly. (The needle feed amount can be adjusted to within 0% to +20% of the lower feed amount.)

Equipped with chain off gauge parts
Mit Abketteilen ausgerüstet
Equipée de pièces de calibrage de chaînette décalée
Equipada con piezas calibradas de cadena libre



- The crosspiece of the needle plate securely presses the chain off, so that the chain off can be formed smoothly. This removes the need to pull the chain off from behind and boosts working efficiency.



Specifications

Model	Double chain stitch	Cylinder type	Needle feed	Height of presser foot	Stitch length	Max. sewing speed
DC-2910	★	★	★	10 mm	4.5 mm	4,500 rpm

DC-2910-

	Application
60	Attaching waistband

	No. of needles
2	2 needles
4	4 needles

	Needle gauge
E1A14	31.8 mm (1½) (2 needles)
E1A38	34.9 mm (1⅓) (2 needles)
U1401	6.4 - 25.4 - 6.4 mm (¼-1-¼) (4 needles)

Options



Presser lifter kit

Increases working efficiency by automatically raising the presser foot when the treadle is pressed lightly backward.



Needle cooler

Stops the temperature of the needle from rising when sewing at high speed, thus preventing thread breakages due to heat.



Impact cutter kit

Cuts the chain off when the knee switch is operated. The tip of the cutter has been made squarer for greater safety.

- All devices are pneumatically driven. In addition, they can be installed to the sewing machine at any time after purchase.

Product specifications are subject to change for improvement without notice. Please read instruction manual before using the machine for safety operation.

brother
BROTHER INDUSTRIES, LTD.

15-1,Naeshiro-cho,Mizuho-ku,Nagoya 467-8561, Japan.
Phone:81-52-824-2177 Fax:81-52-811-7789 http://www.brother.com/

ARCH SEWING
215.627.1768
www.archsewing.com